

~~S. 32° E. 26 links then S. 6° E. 36.24½ Chains to the center of the first line which I run and made a corner at a Beech 17 ins. dia.~~

Ins. dia. N. 26° E. 34½ Links and Hickory 15 Ins. dia. S. 4½° E. 21½ Links Then went Back on last line Run 18.01¼ Chains and made a corner at a stake at a Walnut 7 Ins. dia. S. 36½° E. 23 Links and walnut 5 Ins. dia. N. 8½° W. 33 Links Then N. 84° and about 30° E. 20.15¾ Chains to the second line which I run and made a corner at a stake at a Sugar 10 Ins. dia. N. 36° W. 23½ Links and W. Oak 40 Ins. dia. S. 77½° E. 16½ Links this corner is 18.01½ Chains South of the N.E. Corner of Section on the section line and it is 17.79½ Chains North of the Quarter stake.

Jesse Pickard and David Witty Chain Bearers.

John B. Kelshaw C.S. G. C. Ia.

No 50

December the 5th 6th and 7th 1838. Then Surveyed for John Inman and Samuel R. Cavins In T. 7. N. R. 5. W. Section 26 Beginning at the Quarter Stake on the west side of Section and Surveyed for John Inman the west ½ of the S. W. ¼ of Said Section first S. 6° E. 40.37 Chains to the S. W. corner of Said Section then went East on the Section line to a corner according to the Record of Peter R. Lester 80. rods East of Said Section corner at a stake at a Beech 18 ins. dia. N. 64° E. 18 Links and Beech 10 Ins. dia. N. 32° E. 15 Links Then N. 40 Chains to the S. W. Side of a W. Oak 28 Ins. dia. Corner then went to the East Quarter Stake then S. 84° W. 80.44 Chains to the Section line on the west side of Section and missed the west quarter 2.04½ Links Southward then went to the North Quarter Stake then S. 6° E. 79.44 Chains to the Section line on the South side of Section and missed the South Quarter Stake 3½ Links on the right hand.

# Record of Surveys by John C. Brown, County Surveyor of Greene County Indiana.

April 3rd 1839 Surveyed for H. M. Hobson the E. ½ of the N. W. ¼ of Section 11 in Town 7 North of range 3 west Beginning at the N.E. Corner of Said section thence South 5° 51' E. 79 ch 81 Links then returned 39 ch 90½ then Established a ¼ S. corner (the original being destroyed) Witness trees Hickory 20 N 48½ W. 202 Links Hickory 18 S. 72° W. 226 Then went to ¼ S. on South side of Said Section thence N. 5° 45' W. 79.89 ch. found myself 68 links to the right of ¼ stake on the North and corrected back then went to ¼ S. on East side of Said Section thence S. 84° 15' W. 79 ch 60 Links found myself 136½ to the right of ¼ S. on W. Side corrected variation thence N 83° 45' E. 39.80 Chains and Established ¼ center corner Beyond Witness trees B. Oak 30 N. 70° W. W. Oak 20.21½ E. then went Back on said line 19.90 ch and established ½ S stone Wts W. Oak 14 N 6° W 51 Links white Oak 10 N 39° 30 Links thence N. 5° 52' W 39.36 ch nor to sec. line on north side (being the dividing between E and W ½ of the N. W. ¼ of Said Section being Division line between H. M. Hobson & John Crane the latter consenting to Said survey) then Established ¼ S. Equi distant from the N. W. ful corner & ¼ S. on North Side Wits trees Beach 20 S 61 E 68 Sugar tree 10 S. 22° 15' W 68. John C. Brown County Survey.

April 4th 1839 Surveyed for John Crane beginning at the ¼ S on the N. Side of Sec 11 in town Range 3 west thence N 85° 10' E to N.E. Corner of said section 40.14 Chains returned on Said line 20.7 chains Established ½ S Stone corner Sugar tree 12 N. 65° W 28½ Links Sugar 24 N 23° W 26½ links Then went to ¼ S on East [ ] of said Sec. thence S. 83° 45' W. 39.65 ch to center [ ] ¼ stake of said section then returned on Said line [ ] chains Established ¼ S Witness W oak 24 N 3½ W 43 [ ] W Oak 33 N 43° E 39 Links poplar 10 S 76° W 74½ lin [ ] Beech 6 S 180° E 15½ Links

(The words belonging in the spaces enclosed as follows [ ] were torn out of the old Record. Blotted)

Then N 6° W 39.85 ch. to ¼ on the north side of the N. E. 2d of